

630

Counting Scales



- ◆ **Highly Visible Green VFD Display**– Scale display can easily be viewed from up to 20" away. The three displays simultaneously show Gross Weight, APW, and Piece Count.
- ◆ **Highly Durable**– Easily withstands the rigors of industrial applications, utilizing an ABS case, an all steel frame, and a stainless steel/ABS weight platter.
- ◆ **RS-232 Port**– Provides transmission of an APW to the TC-2001, TC-2005 or 650. Also provides transmission to a printer, computer, remote display or other compatible devices.
- ◆ **1:600,000 Internal Resolution**– High internal resolution provides greater sensitivity, for increased counting accuracy and weighments.
- ◆ **22 Key Tactile Keypad**– The 22 key membrane panel allows entry of numeric data, such as known tare values, APW's, and specific sample sizes from 1 to 999,999.



630 Counting Scale

Specifications

CAPACITIES & SIZES			
630-6	6 x 0.0005 lb 3000 x 0.2 kg	630-30	30 x 0.002 lb 15 x 0.001 kg
630-12	12 x 0.001 lb 6000 x 0.5 kg	630-60	60 x 0.005 lb 30 x 0.002 kg

Dimensions—

Scale: 13.39" (L) x 10.63" (W) x 3.94" (H)
(340mm x 270mm x 100mm)

Weighing Platform: 10.04" x 8.86"
(255mm x 225mm)

Display— 16 Character, 7-Segment Green Vacuum Fluorescent (VFD).

APW Transfer— The APW can be transferred to the TC-2001, TC-2005, or 650 utilizing the RS-232 port.

Counting Capacity— 999,999

Weighing Resolution— 1 part in 500 to 1:50,000 max

Keyboard Setup and Calibration— Calibration and setup parameters all keyboard accessible, for easy installation.

Units of Measure— lb / kg

Operating Temperature— 0° C to 40° C, 32° F to 104° F

Power Requirements— AC Adapter, 12 VDC, 800mA, included.

Housing— ABS

Base and Sub Platform— Metal

Platform— ABS/Stainless Steel top.

Feet— Non-Skid Hard Rubber.

Shipping Weight— 16 pounds (7.2 kg)

Accumulation Function— Can accumulate either pieces or weight, and print total.



Salter Brecknell Weighing Products

a division of Avery Weigh-Tronix
1000 Armstrong Dr.
Fairmont, MN 56031
Toll free: 800-637-0529
Tel: 507-238-8702 Fax: 507-238-8271
e-mail: sales@salterbrecknell.com
www.salterbrecknell.com